

# VIGOROUS AT606

# HIFLY TIRES

Rim Diameter	Factory Code	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Road Condition	UTQG	Rolling Resistance	Wet Grip	Noise	
								in	mm	in	mm	Single		Dual		psi	kpa	32nd	mm	lbs	kg					db	Level
												lbs	kg	lbs	kg												
15"	201H7017	265/70R15	10	E	112T	T	7 1/2J	10.7	272	29.6	753	2469	1120	-	-	44	300	13	10	34.6	15.7	M+S	460 A B	D	D	72	B
16"	201H7018	245/70R16	-	-	107	T	7J	9.8	248	29.5	750	2150	975	-	-	44	300	13	10	33.6	15.2	M+S	460 A B	D	D	71	B
	201H7019	255/70R16	-	-	111	T	7 1/2J	10.2	260	30.1	764	2403	1090	-	-	44	300	13	10	34.7	15.8	M+S	460 A B	D	D	72	B
	201H7020	265/70R16	-	-	112	T	8J	10.7	272	30.6	778	2469	1120	-	-	44	300	13	10	36.6	16.6	M+S	460 A B	D	D	72	B
17"	201H7029	265/65R17	-	-	112	T	8J	10.7	272	30.6	776	2469	1120	-	-	44	300	13	10	36.6	16.6	M+S	460 A B	D	D	72	B
18"	201H7012	265/60R18	-	-	110	T	8J	11.3	287	31.5	801	2601	1180	-	-	44	300	13	10	37.9	17.2	M+S	460 A B	D	D	72	B
	201H7010	265/65R18	-	-	114	T	8J	11.3	287	32.0	812	2755	1250	-	-	44	300	13	10	39.7	18.0	M+S	460 A B	D	D	72	B
	201H7011	275/65R18	-	-	116	T	8J	10.7	272	30.5	775	2337	1060	-	-	44	300	13	10	37.3	16.9	M+S	460 A B	D	D	72	B
20"	201H7013	275/55R20	-	-	113	H	8 1/2J	11.2	284	31.9	810	2535	1150	-	-	44	300	13	10	41.7	18.9	M+S	460 A B	D	D	72	B
<b>LIGHT TRUCK</b>																											
18"	201H7014	LT275/65R18	10	E	123/120	S	8J	11.0	279	32.1	815	3410	1550	3085	1400	80	550	16	13	49.7	22.6	M+S	-	-	-	-	-
	201H7002	LT265/70R18	10	E	124/121	S	8J	10.7	272	32.6	829	3525	1600	3195	1450	80	550	16	13	50.2	22.8	M+S	-	-	-	-	-
	201H7003	LT275/70R18	10	E	125/122	R	8J	11.0	279	33.2	843	3640	1650	3305	1500	80	550	16	13	52.3	23.7	M+S	-	-	-	-	-
20"	201H7015	LT275/65R20	10	E	126/123	R	8J	11.0	279	34.1	866	3750	1700	3415	1550	80	550	16	13	53.7	24.4	M+S	-	-	-	-	-