

Win-transit



Rim Diameter	Factory Code	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Stud Size TSMI	Road Condition	UTQG	Rolling Resistance	Wet Grip	Noise	
								in	mm	in	mm	lbs	kg	lbs	kg	psi	kpa	32nd	mm	lbs	kg						db	Level
								Single		Dual																		
15"	300H5001	195/70R15C	8	D	104/102	R	6J	7.9	201	25.8	655	2094	950	1984	900	65	450	12	10	24.3	11.0	-	M+S	-	D	D	73	B
	300H5002	215/70R15C	8	D	109/107	R	6 1/2J	8.7	221	26.9	683	2271	1030	2149	975	65	450	12	10	27.1	12.3	-	M+S	-	D	D	73	B
	300H5012	215/65R15C	6	C	104/102	R	6 1/2J	8.7	221	26.0	661	1984	900	1874	850	54	375	12	10	25.8	11.7	-	M+S	-	D	D	73	B
16"	300H5003	225/70R15C	8	D	112/110	R	6 1/2J	9.0	228	27.4	697	2469	1120	2337	1060	68	475	12	10	28.8	13.1	-	M+S	-	D	D	73	B
	300H5004	195/75R16C	8	D	107/105	R	5 1/2J	7.7	196	27.5	698	2149	975	2039	925	68	475	11	9	26.6	12.1	-	M+S	-	D	D	73	B
	300H5005	195/65R16C	8	D	104/102	R	6J	7.9	201	23.6	600	1984	900	1874	850	68	475	12	10	24.6	11.2	-	M+S	-	D	D	73	B
	300H5009	195/60R16C	6	C	99/97	T	6J	7.9	201	25.2	640	1709	775	1609	730	54	375	12	10	23.4	10.6	-	M+S	-	D	D	73	B
	300H5006	205/65R16C	8	D	107/105	R	6J	8.2	209	26.5	672	2149	975	2039	925	68	475	12	10	26.4	12.0	-	M+S	-	D	D	73	B
	300H5007	215/65R16C	8	D	109/107	R	6 1/2J	8.7	221	27.0	686	2271	1030	2149	975	68	475	12	10	28.0	12.7	-	M+S	-	D	D	73	B
	300H5010	215/60R16C	8	D	108/106	R	6 1/2J	8.7	221	26.1	664	2205	1000	2094	950	68	475	12	10	28.1	12.7	-	M+S	-	D	D	73	B
	300H5013	225/65R16C	8	D	112/110	R	6 1/2J	9.0	228	27.5	698	2469	1120	2337	1060	68	475	12	10	30.4	13.8	-	M+S	-	D	D	73	B
300H5008	235/65R16C	8	D	115/113	R	7J	9.5	240	28.0	712	2679	1215	2535	1150	68	475	12	10	31.7	14.4	-	M+S	-	D	D	73	B	
300H5011	215/75R16C	10	E	116/114	R	6J	8.5	216	28.7	728	2756	1250	2601	1180	76	525	12	10	32.1	14.6	-	M+S	-	D	D	73	B	