

VIGOROUS MT602

HIFLY TIRES

Rim Diameter	Factory Code	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Road Condition	UTQG	Rolling Resistance	Wet Grip	Noise	
								in	mm	in	mm	Single		Dual		psi	kpa	32nd	mm	lbs	kg					db	Level
										lbs	kg	lbs	kg														
15"	201H8001	31X10.50R15LT	6	C	109	Q	8 1/2J	10.6	268	30.7	781	2271	1030	-	-	50	350	18	15	42.5	19.3	M+S	-	-	-	-	-
	201H8006	33x12.50R15LT	6	C	108	Q	10J	12.5	318	32.8	832	2205	1000	-	-	35	250	18	15	51.1	23.2	M+S	-	-	-	-	-
16"	201H8002	LT235/75R15	6	C	104/101	Q	6 1/2J	9.3	235	29.1	739	1984	900	1819	825	50	350	18	15	38.1	17.3	M+S	-	-	-	-	-
	201H8003	LT245/75R16	10	E	120/116	Q	7J	9.8	248	30.7	780	3042	1380	2778	1260	80	550	18	15	45.4	20.6	M+S	-	-	-	-	-
17"	201H8005	LT265/75R16	10	E	123/120	Q	7 1/2J	10.5	267	31.9	810	3417	1550	3086	1400	80	550	18	15	50.9	23.1	M+S	-	-	-	-	-
	201H8009	LT265/65R17	10	E	120/117	Q	8J	10.7	272	30.8	782	3086	1400	2833	1285	80	550	18	15	47.6	21.6	M+S	-	-	-	-	-
18"	201H8004	LT265/70R17	10	E	121/118	Q	8J	10.7	272	31.9	810	3197	1450	2910	1320	80	550	18	15	51.4	23.3	M+S	-	-	-	-	-
	201H8010	LT265/60R18	10	E	119/116	Q	8J	10.7	272	30.7	781	2998	1360	2756	1250	80	550	18	15	47.2	21.4	M+S	-	-	-	-	-
20"	201H8007	33x12.50R20	10	E	114	Q	10J	12.5	318	32.8	832	2601	1180	-	-	65	450	20	16	57.1	25.9	M+S	-	-	-	-	-
	201H8008	35x12.50R20	10	E	121	Q	10J	12.5	318	34.8	883	3197	1450	-	-	65	450	20	16	61.9	28.1	M+S	-	-	-	-	-