

SUPER5000



Rim Diameter	Factory Code	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Road Condition	UTQG	Rolling Resistance	Wet Grip	Noise	
								in	mm	in	mm	Single		Dual		psi	kpa	32nd	mm	lbs	kg					db	Level
												lbs	kg	lbs	kg												
12"	201H9002A	155R12C-8PR	8	D	88/86	Q	4.50B	6.2	157	21.7	550	1235	560	1168	530	65	450	8	7	11.9	5.4	M+S	-	C	C	72	B
14"	201H9008	185R14C-8PR	8	D	102/100	R	5 1/2J	7.4	188	25.6	650	1874	850	1764	800	65	450	9	7	19.4	8.8	M+S	-	C	C	72	B
	201H9010	195R14C-8PR	8	D	106/104	R	5 1/2J	7.8	198	26.2	666	2094	950	1984	900	65	450	9	8	20.5	9.3	M+S	-	C	C	72	B
15"	201H9012	195R15C-8PR	8	D	106/104	R	5 1/2J	7.8	198	27.3	693	2094	950	1984	900	65	450	9	8	21.6	9.8	M+S	-	C	C	72	B
	201H9033	225/70R15C-8PR	8	D	112/110	R	6 1/2J	9.0	228	27.4	697	2469	1120	2337	1060	65	450	13	10	25.0	11.3	M+S	-	C	C	72	B