

# VIGOROUS AT601



Rim Diameter	Factory Code	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Road Condition	UTQG	Rolling Resistance	Wet Grip	Noise	
								in	mm	in	mm	Single		Dual		psi	kpa	32nd	mm	lbs	kg					db	Level
												lbs	kg	lbs	kg												
15"	200H7030	215/75R15	-	-	100	S	6J	8.5	216	27.7	703	1764	800	-	-	44	300	12	10	25.6	11.6	M+S	460AB	D	D	71	B
	200H7024	235/75R15	XL	-	109	S	6 1/2J	9.3	235	28.9	733	2271	1030	-	-	50	340	13	10	31.3	14.2	M+S	460AB	D	D	72	B
	200H7032	205/80R16	XL	-	104	T	5 1/2J	8.0	203	28.9	734	1984	900	-	-	50	340	11	9	27.6	12.5	M+S	460AB	D	D	72	B
	200H7017	235/70R16	-	-	106	T	7J	9.4	240	29.0	736	2094	950	-	-	44	300	13	10	31.3	14.2	M+S	460AB	D	D	71	B
	200H7018	245/70R16	-	-	107	T	7J	9.8	248	29.5	750	2150	975	-	-	44	300	13	10	32.7	14.8	M+S	460AB	D	D	71	B
	200H7019	255/70R16	-	-	111	T	7 1/2J	10.2	260	30.1	764	2403	1090	-	-	44	300	13	10	34.1	15.5	M+S	460AB	D	D	72	B
	200H7020	265/70R16	-	-	112	T	8J	10.7	272	30.6	778	2469	1120	-	-	44	300	13	10	35.7	16.2	M+S	460AB	D	D	72	B
16"	200H7025	245/75R16	-	-	111	S	7J	9.8	248	30.5	774	2403	1090	-	-	44	300	13	10	33.8	15.4	M+S	460AB	D	D	71	B
	200H7026	265/75R16	-	-	116	S	7 1/2J	10.5	267	31.7	804	2755	1250	-	-	44	300	13	10	38.1	17.3	M+S	460AB	D	D	72	B
	200H7016	245/65R17	-	-	107	T	7J	9.8	248	29.5	750	2150	975	-	-	44	300	13	10	32.4	14.7	M+S	460AB	D	D	71	B
	200H7029	265/65R17	-	-	112	T	8J	10.7	272	30.6	776	2469	1120	-	-	44	300	13	10	35.8	16.2	M+S	460AB	D	D	72	B
	200H7021	245/70R17	-	-	110	T	7J	9.8	248	30.6	776	2337	1060	-	-	44	300	13	10	34.4	15.6	M+S	460AB	D	D	71	B
	200H7022	265/70R17	-	-	115	T	8J	10.7	272	31.7	804	2679	1215	-	-	44	300	13	10	37.3	16.9	M+S	460AB	D	D	72	B
	200H7023	P285/70R17	-	-	117	T	8 1/2J	11.5	292	32.8	832	2833	1285	-	-	44	300	13	10	40.6	18.4	M+S	460AB	D	D	74	B
<b>LIGHT TRUCK</b>																											
15"	200H7001	31x10.50R15LT	6	C	109	R	8 1/2J	10.6	268	30.5	775	2270	1030	-	-	50	350	16	13	39.4	17.9	M+S	-	D	D	72	B
	200H7031	225/75R15C	6	C	110/108	S	6J	8.8	223	28.3	719	2337	1060	2205	1000	54	375	16	13	33.2	15.1	M+S	-	-	-	-	-
	200H7028	LT215/75R15	6	C	100/97	S	6J	8.5	216	27.7	703	1765	800	1610	730	50	350	16	13	28.7	13.0	M+S	-	D	D	72	B
	200H7003	LT235/75R15	6	C	104/101	R	6 1/2J	9.3	235	28.9	733	1985	900	1820	825	50	350	16	13	34.1	15.5	M+S	-	D	D	72	B
	200H7010	LT255/70R15	6	C	107/103	S	7 1/2J	10.2	260	29.1	739	2150	975	1930	875	50	350	16	13	38.4	17.4	M+S	-	D	D	72	B
	200H7011	LT265/70R15	6	C	109/105	S	8J	10.7	272	29.6	753	2270	1030	2040	925	50	350	16	13	39.5	17.9	M+S	-	D	D	72	B
	200H7012	LT245/70R16	8	D	113/110	S	7J	9.8	248	29.5	750	2535	1150	2335	1060	65	450	16	13	38.3	17.4	M+S	-	D	D	72	B
16"	200H7013	LT265/70R16	8	D	117/114	S	8J	10.7	272	30.6	778	2835	1285	2600	1180	65	450	16	13	41.3	18.7	M+S	-	D	D	72	B
	200H7014	LT275/70R16	8	D	119/116	S	8J	11.0	279	31.2	792	3000	1360	2755	1250	65	450	16	13	45.2	20.5	M+S	-	D	D	72	B
	200H7008	LT215/85R16	10	E	115/112	R	6J	8.5	216	30.4	772	2680	1215	2470	1120	80	550	16	13	37.7	17.1	M+S	-	D	D	72	B
	200H7009	LT235/85R16	10	E	120/116	R	6 1/2J	9.3	235	31.7	806	3042	1380	2778	1260	80	550	16	13	43.7	19.8	M+S	-	D	D	72	B
	200H7004	LT225/75R16	10	E	115/112	S	6J	8.8	223	29.3	744	2680	1215	2470	1120	80	550	16	13	36.5	16.5	M+S	-	D	D	72	B
	200H7005	LT245/75R16	10	E	120/116	S	7J	9.8	248	30.5	774	3042	1380	2778	1260	80	550	16	13	42.4	19.3	M+S	-	D	D	72	B
	200H7006	LT265/75R16	10	E	123/120	R	7 1/2J	10.5	267	31.7	804	3415	1550	3085	1400	80	550	16	13	46.5	21.1	M+S	-	-	-	-	-
17"	200H7015	LT285/75R16	10	E	126/123	R	8J	11.3	286	32.8	834	3750	1700	3415	1550	80	550	16	13	50.9	23.1	M+S	-	-	-	-	-
	200H7007	LT245/75R17	10	E	121/118	S	7J	9.8	248	31.5	800	3195	1450	2910	1320	80	550	16	13	43.5	19.7	M+S	-	D	D	72	B
	200H7002	LT265/70R17	10	E	121/118	S	8J	10.6	272	31.7	804	3195	1450	2910	1320	80	550	16	13	45.9	20.8	M+S	-	D	D	72	B
	200H7027	LT285/70R17	10	E	121/118	R	8 1/2J	11.5	292	32.8	832	3195	1450	2910	1320	80	550	16	13	52.9	24.0	M+S	-	D	D	72	B