

Ice-transit



Rim Diameter	Factory Code	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Stud Size TSMI	Road Condition	UTQG	Rolling Resistance	Wet Grip	Noise	
								in	mm	in	mm	lbs	kg	lbs	kg	psi	kpa	32nd	mm	lbs	kg						db	Level
								Single		Dual																		
12"	300H6003	155R12C	8	D	88/86	Q	4.50B	6.2	157	21.7	550	1235	560	1168	530	65	450	11	9	13.5	6.1	11	M+S	-	D	D	73	B
13"	300H6004	165R13C	8	D	94/92	R	4.50B	6.6	167	23.5	598	1477	670	1389	630	65	450	11	9	17.4	7.9	11	M+S	-	D	D	73	B
	300H6007	175R13C	8	D	97/95	R	5.00B	7.0	178	24.0	610	1609	730	1521	690	65	450	11	9	19.4	8.8	11	M+S	-	D	D	73	B
	300H6006	155R13C	8	D	90/88	Q	4.50B	6.2	157	22.8	578	1323	600	1235	560	65	450	11	9	15.9	7.2	11	M+S	-	D	D	73	B
14"	300H6001	185R14C	8	D	102/100	R	5 1/2J	7.4	188	25.6	650	1874	850	1764	800	65	450	11	9	21.4	9.7	11	M+S	-	D	D	73	B
	300H6005	175R14C	8	D	99/98	R	5J	7.0	178	25.0	634	1709	775	1653	750	65	450	11	9	19.2	8.7	11	M+S	-	D	D	73	B
15"	300H6010	195/70R15C	8	D	104/102	R	6J	7.9	201	25.8	655	1984	900	1874	850	65	450	12	10	25.0	11.3	11	M+S	-	D	D	73	B
16"	300H6002	185/75R16C	8	D	104/102	R	5J	7.2	184	26.9	684	2149	900	2039	850	68	475	12	10	25.3	11.5	11	M+S	-	D	D	73	B
	300H6008	205/65R16C	8	D	107/105	T	6J	8.2	209	26.5	672	2149	975	2039	925	68	475	12	10	27.0	12.3	11	M+S	-	D	D	73	B
	300H6009	215/65R16C	8	D	109/107	T	6 1/2J	8.7	221	27.0	686	2271	1030	2149	975	68	475	12	10	29.0	13.2	11	M+S	-	D	D	73	B