

ALL-transit



Rim Diameter	Factory Code	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Road Condition	UTQG	Rolling Resistance	Wet Grip	Noise	
								in	mm	in	mm	Single		Dual		psi	kpa	32nd	mm	lbs	kg					db	Level
												lbs	kg	lbs	kg												
14"	500H2015	175/70R14LT	6	C	95/93	S	5J	7.0	177	23.7	602	1521	690	1433	650	54	375	11	9	17.6	8.0	M+S	-	D	D	73	B
15"	500H2004	195/70R15C	8	D	104/102	R	6J	7.9	201	25.8	655	1984	900	1874	850	65	450	12	10	24.9	11.3	M+S	-	D	D	73	B
	500H2005	215/70R15C	8	D	109/107	R	6 1/2J	8.7	221	26.9	683	2271	1030	2149	975	65	450	12	10	27.2	12.3	M+S	-	D	D	73	B
	500H2012	215/65R15C	6	C	104/102	T	6 1/2J	8.7	221	26.1	664	1984	900	1874	850	54	375	12	10	27.8	12.6	M+S	-	D	D	73	B
16"	500H2013	225/70R15C	8	D	112/110	R	6 1/2J	9.0	228	27.4	697	2469	1120	2337	1060	65	450	12	10	30.3	13.7	M+S	-	D	D	73	B
	500H2006	195/75R16C	8	D	107/105	R	5 1/2J	7.7	196	27.5	698	2149	975	2039	925	68	475	12	10	26.8	12.1	M+S	-	D	D	73	B
	500H2001	195/65R16C	8	D	104/102	R	6J	7.9	201	26.0	660	1984	900	1874	850	68	475	12	10	24.6	11.2	M+S	-	D	D	73	B
	500H2010	195/60R16C	6	C	99/97	T	6J	7.9	201	25.2	640	1709	775	1609	730	54	375	12	10	23.4	10.6	M+S	-	D	D	73	B
	500H2016	205/75R16C	10	E	113/111	R	5 1/2J	8.0	203	28.1	714	2535	1150	2403	1090	76	525	12	10	29.8	13.5	M+S	-	D	D	73	B
	500H2002	205/65R16C	8	D	107/105	T	6J	8.2	209	26.5	672	2149	975	2039	925	68	475	12	10	27.0	12.3	M+S	-	D	D	73	B
	500H2007	215/75R16C	10	E	116/114	R	6J	8.5	216	28.7	728	2756	1250	2601	1180	76	525	12	10	31.7	14.4	M+S	-	D	D	73	B
	500H2003	215/65R16C	8	D	109/107	T	6 1/2J	8.7	221	27.0	686	2271	1030	2149	975	68	475	12	10	28.9	13.1	M+S	-	D	D	73	B
	500H2011	215/60R16C	8	D	108/106	T	6 1/2J	8.7	221	26.0	661	2205	1000	2094	950	68	475	12	10	25.7	11.6	M+S	-	D	D	73	B
	500H2008	225/75R16C	12	F	121/120	R	6J	8.8	223	29.3	744	3195	1450	2535	1400	83	575	12	10	33.7	15.3	M+S	-	D	D	73	B
500H2014	225/65R16C	8	D	112/110	R	6 1/2J	9.0	228	27.5	698	2469	1120	2337	1060	68	475	12	10	30.2	13.7	M+S	-	D	D	73	B	
500H2009	235/65R16C	8	D	115/113	T	7J	9.4	240	28.0	712	2697	1215	2535	1150	68	475	12	10	31.9	14.5	M+S	-	D	D	73	B	